

Datasheet

STREAM-A

Gateway	
Cell interface	LTE CAT 1
Hz 4G LTE	LTE-FDD Band 2/4/5/12/13/25/26 WCDMA Band 2/4/5
Carriers	T-Mobile, AT&T, or Verizon
SIM interface	Dual-SIM (micro)
Cell antenna port	SMA (2x)
Ethernet	10/100BASE-T RJ45 (2x)
Storage	8GB
LEDs	- Network - Signal Strength - Power - Status - Error/Warning
Serial	RS485, RS232
Protocols	Modbus RTU/TCP (Master/Slave), EtherNet/IP, ISO-on-TCP, OPC UA Client/Server, etc.

PLC	
Com. Ports	Ethernet RJ45 (1) RS-232 RJ12 (1) MicroB-USB (1)
Protocols	- Modbus RTU/TCP (Master/Slave), - ASCII In/out - EtherNet/IP
Programming	Ladder Logic

I/O Configuration Options*

Digital Inputs	20 (12-24V DC sinking) 2 commons
Analog Inputs	12 (4-20mA, 0-5V, 0-10V) 2 common
Digital Outputs	10 (0-250V AC, 0-30V DC)
Analog Outputs	6 (4-20mA source, 0-10V)

* **Alternative IO card options available on request**

Power

Power supply (UL-rated)	120V AC -> 24V DC
7 Ah battery (UPS managed)	>8 hours of backup power
Circuit breaker	4A

Dimensions	
L x W x H	23 x 15 x 7.1 in 584 x 381 x 180 mm

Weight	28 LBS
---------------	--------

Enclosure	
NEMA rating	1, 2, 3, 3R, 3X, 3RX, 3S, 3SX, 4, 4X, 5, 6*, 6P*, 12 & 13
IP rating	IP65, IP66, IP67* & IP68
Safety feature	Lockable clasp
Mounting options	Pole, DIN, Wall Bracket

* **Alternative enclosures available on request**

Environmental Conditions	
Operating temperature	(-20) to 70 °C (-4) to 158 °F

On-Device Analytical Capabilities	
Pump monitoring	Daily runtime & cycle counting
Flow totalization	Based on pulse counting and analog input
Data posts	Scheduled (configurable) Alarm-based (real-time)
AI-Flows	AI-based flow predictions for lift stations

Software	
Software-as-a-Service	
Latest version of a supported browser required.	

Warranty	
1-year parts & labor	

